

Material Safety Data Sheet



Zep Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-I-BUY-ZEP (428-9937)
www.zep.com

Section 1. Chemical Product and Company Identification

Product name ASPHALT AND TAR REMOVER
Product use Solvent Cleaner
Product code 1069
Date of issue 06/16/09 **Supersedes** 04/26/05

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318


Printing date: 06/16/09

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

DANGER !



COMBUSTIBLE. CAUSES EYE AND SKIN IRRITATION. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Eye contact. Inhalation.

Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin

Causes skin irritation. May cause skin sensitization. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation

Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression. Inhalation causes headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.

Ingestion

May be fatal if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Prolonged or repeated contact may dry skin and cause irritation. Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation. Contains material which may cause damage to the following organs: blood, kidneys, liver, heart, central nervous system (CNS), ears, testes.

Carcinogenicity

No known significant effects or critical hazards.

Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
LIGHT AROMATIC NAPHTHA; aromatic hydrocarbon solvent; solvent naphtha (petroleum)	64742-95-6	40 - 50
D-LIMONENE; orange distillate; citrus terpene; cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)-	5989-27-5	20 - 30
1,2,4-TRIMETHYLBENZENE	95-63-6	10 - 20
KEROSENE; techsene; fuel oil; coal oil	8008-20-6	10 - 20
NONYLPHENOXY POLY(ETHYLENEOXY) ETHANOL - npe; poly(oxy-1,2-ethanediy)l alpha-(nonylphenyl)-omega-hydroxy	9016-45-9	1 - 10

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
Skin Contact	Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Get medical attention if irritation develops.
Inhalation	Move exposed person to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Ingestion	Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Closed cup: 39.44°C (103°F)
Flammable Limits	Not available.
Flammability	COMBUSTIBLE LIQUID AND VAPOR.
Fire hazard	COMBUSTIBLE. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. May emit toxic fumes under fire conditions. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Fire-Fighting Procedures	Use dry chemical, CO ₂ , water spray (fog) or foam.

Section 6. Accidental Release Measures

Spill Clean up	Eliminate all ignition sources. Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
-----------------------	--

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Empty containers retain product residue and can be hazardous. Do not reuse container. Observe label precautions. Wash thoroughly after handling.
Storage	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Do not store in unlabeled containers. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

1,2,4-TRIMETHYLBENZENE

KEROSENE; techsene; fuel oil; coal oil


Exposure limits**ACGIH TLV (United States).**

TWA: 25 ppm 8 hour(s).

OSHA PEL (United States).

TWA: 25 ppm 8 hour(s).

ACGIH TLV (United States).TWA: 200 mg/m³ 8 hour(s). Form: Total Hydrocarbon Vapor**Personal Protective Equipment (PPE)**

Eyes	Splash goggles.	
Body	Wear appropriate protective clothing to prevent skin contact. Recommended: Nitrile gloves. Neoprene gloves. Rubber gloves.	
Respiratory	Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.	

Section 9. Physical and Chemical Properties

Physical State Liquid.
pH Not applicable
Boiling Point 126.7°C (260.1°F)
Specific Gravity 0.879
Solubility Emulsifies in water.

Color Brown.
Odor Solvent-like.
Vapor Pressure Not determined.
Vapor Density >1 [Air = 1]
Evaporation Rate Not determined.
VOC (Consumer) 509 (g/l). 4.25 lbs/gal (58.0%)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.
Incompatibility Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.
 Slightly reactive or incompatible with the following materials: acids and alkalis.
Hazardous Polymerization Not available.
Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Light Aromatic Naphtha	LD50 Oral	Rat	4700 mg/kg	-
	LC50 Inhalation Vapor	Rat	3670 ppm	8 hours
Kerosene	LD50 Dermal	Rat	4000 mg/kg	-
	LD50 Oral	Rat	8000 mg/kg	-
1,2,4-Trimethylbenzene	LD50 Oral	Rat	5000 mg/kg	-
Nonylphenoxypoly(Ethyleneoxy)Ethano	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	3310 mg/kg	-

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.
Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D001
 Classification: - [Hazardous waste]
 Origin: - [RCRA waste.]

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Not a DOT controlled material (United States).	-		

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

1,2,4-Trimethylbenzene

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65

WARNING: This product contains a chemical or chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. :
Benzene, Toluene, Naphthalene

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.