

PRODUCT SPECIFICATION REPORT

Dry Moly uses molybdenum disulfide to create a superior, long-lasting,

dry lubricating film which will hold up under extreme conditions of temperature and pressure.

DRY MOLY PROD.#0094

Aerosol Dry Film Lubricant



FEATURES/BENEFITS:

Molybdenum Disulfide	Stabilized, micronized dispersion of molybdenum disulfide provides effective lubrication at temperatures up to 750°F and pressure loads greater than 20,000 psi. Reduces friction and wear for metal-to-metal contact points.
Dry Film Lubrication	Convenient aerosol sprays a thin, black coating that adheres readily to most surfaces and dries within seconds without leaving an oily or tacky film which can attract dirt and dust
Anti-Seize	Prevents galling and seizing of threaded parts.
Protective Coating	Finish adheres well to all metals, most plastics, and rubber to provide long-lasting lubrication protection

APPLICATIONS:

For lubricating moving parts of all kinds, especially those subjected to high temperatures and very heavy loads, such as conveyors, bearings, high-speed gears, pump assemblies, machine tools. For lubrication of mining, farm machinery or construction equipment, particularly when dust or abrasive materials are present. Recommended for use to: Automotive Repair Facilities, Manufacturing, Metal Fabrication Shops, Equipment Repair & Rental, and Farm Machinery & Equipment

COMPANION PRODUCTS:

Tuff Green(GreenLink), Zepride, I.D. Flush, I.D. Clean, Zep 45, ML Lubricant, Red Slide, Flash, Dyna 143, Ultrawipes, Zep Gloves & Safety Glasses

SPECIFICATIONS:

Physical Form	Aerosol (liquid)
Color	Opaque, Black
Odor	Mild, Solvent-like
Flammability	Non-Flammable by CSMA Flame Extension
Shelf Life	1 Year Minimum
D.O.T. Shipping Label	ORM-D

PACKAGING:

20 fl. oz. can

Zep Sales & Service www.zep.com 1-877 I BUY ZEP