



ZEP EXPRESS WAX

Now with UV Blockers and Rust-Oleum® Protection

DESCRIPTION

Premium, liquid hand wax that cleans while waxing. Contains a blend of carnauba wax, silicones and cleaners. Specifically designed for use on today's high-tech clear coat, acrylic and enamel finishes.

FEATURES

- Easy application
- Long lasting
- Added protection
- No drying necessary
- No abrasives
- Non-streaking

BENEFITS

- Can be applied and removed quickly by hand.
- Zep Express Wax will protect the finish and bead water for a 4-6 week period.
- Formulated with UV blockers and Rust-Oleum® protection to protect vehicle surfaces.
- Can be applied directly to wet surface.
- Will not scratch clear coat surfaces and produces no dusting on wipe-off.
- Will not streak or haze on hard rubber and vinyl surface

APPLICATIONS

Particularly useful for:

Car Washes

New and Used Car Dealers
Truck Rental & Leasing

Passenger Car Rental & Leasing

COMPANION PRODUCTS

Zep Car and Truck Touch-Free Detergent, Zep Concentrated Rinse Wax, Zep Tireless Shine, Zep Underbody Rust Inhibitor, Zep Protect-All, Zep Re-Tire, Zep Blue Magic, Zep Foam Brush Shampoo, Zep Brite White Foam Shampoo, Zep Foaming Tunnel Cleaner

SPECIFICATIONS

| | | | |
|--------------------------|--------------------------|--------------------------------------|-------------------|
| Physical Form | Moderately thick, liquid | Density - Specific Gravity | 7.9 lbs/gl -0.950 |
| Color | White | Flash Point (TCC) | 100°F |
| Fragrance | Vanilla | Shelf Life | 1 year minimum |
| pH Concentrate | 9.0 to 9.5 | D.O.T. Shipping Label | None |

PACKAGING

Quarts
Gallons



ZEP EXPRESS WAX

Now with UV Blockers and Rust-Oleum® Protection

PROD. #0825
301B



ZEP MANUFACTURING COMPANY
ATLANTA, GA 30301
A division of Acuity Specialty Products Group, Inc.
CLEAN ACROSS AMERICA
AND THROUGHOUT THE WORLD™



BEFORE USING THIS PRODUCT,
PLEASE READ THIS ENTIRE LABEL.

KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL AND INSTITUTIONAL
USE ONLY
NOT FOR HOUSEHOLD USE OR RESALE

PRECAUCION
AL USUARIO: Si usted no lee inglés, no use este
producto hasta que la etiqueta le haya sido
explicada ampliamente.
(TO THE USER: If you cannot read English, do
not use this product until the label has been fully
explained to you.)

HAZARD RATINGS
This product is classified as a irritant and
is not for use by trained personnel. See
the label directions and instructions for
use. Do not use this product if you are
responsible for any injury, loss of, or damage
to property. Do not use this product in
any manner not in compliance with label
directions.

| | | |
|-------------------------------------|---|------------------------------|
| PERSONAL PROTECTION EQUIPMENT | B | Safety Glasses, Gloves |
| | | |

ZEP EXPRESS WAX IMPROVED

Now with Rust-Oleum® Protection and UV Blockers
Ready-To-Use Vehicle Hand Wax

Zep Express Wax is specifically designed for use on today's high-tech clear coat, acrylic and enamel finishes. It's an easy-to-use product that removes residual deposits of tar, grease, oil, and road grime while waxing the surface of the vehicle. Zep Express Wax can be applied to a wet surface and leaves an easy to remove haze. It will not streak glass or haze on hard rubber and vinyl surfaces. It's a great product to use when convenience and time are the top requirements or when a quick, durable shine is needed.

- Zep Express Wax will protect the finish and bead water for a 4 to 6 week period.
- Can be applied and removed quickly by hand.
- Delivers high shine.
- Great to use when a quick, clean shine is required.
- Contains a blend of silicones, carnauba wax and cleaners.

DIRECTIONS:

Shake well before using. For best results, pre-clean the surface to remove any oxidation before applications. Zep Express Wax can be applied by hand with a soft, damp cloth. Let dry to a haze and then buff to a high gloss with a clean, dry cloth.

**WARNING!
COMBUSTIBLE**

Can cause severe eye irritation or inflammation. Inhalation of vapors may cause respiratory tract irritation and/or mid central nervous system depression characterized by headache, dizziness, nausea, or stupor. DO NOT swallow this product. Avoid breathing vapors. Exposure may aggravate existing skin or respiratory disorders. Further information on the effects of overexposure is included on the Material Safety Data Sheet, which is available upon request.

Zep advocates limiting exposure to all chemical products. Wearing of tight-fitting safety glasses is strongly recommended, especially for contact lens wearers. Wear natural rubber, nitrile, neoprene, or

other resistant gloves. Use product in well-ventilated areas only; open windows/doors and use exhaust fans in enclosed spaces. Remove contaminated clothing promptly and DO NOT rewear until thoroughly cleaned. After handling, wash hands thoroughly with soap and water.

FIRST AID:

EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

SKIN: Wash contaminated skin immediately and thoroughly with soap or mild detergent apply a skin cream. Consult a physician if irritation develops.

INHALATION: Move exposed person to fresh air. If irritation persists, get medical attention immediately.

INGESTION: If product is swallowed, DO NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration (breathing) of liquid into the lungs. Get emergency medical attention immediately.

DISPOSAL AND/OR SPILL INFORMATION: As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted to a collection vessel and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, absorb product on an inert absorbent material, such as Zep-O-Zorb or Zep Super Sorbent and deposit in a sealable container. Thoroughly clean area with detergent solution and rinse well with water.

COMBUSTIBLE: Keep away from heat, spark, open flame or any source of ignition.

STORAGE: Store in a cool area away from direct sunlight and protect from freezing. Keep container tightly closed at all times when not in use to decrease evaporation of volatile solvents.

