



## PRODUCT SPECIFICATION REPORT

# ZEP GREASE MONKEY™

## Cleans, Penetrates, Lubricates and Protects

### DESCRIPTION

Penetrating lubricant aerosol. Dries to a non-sticky, viscous, long-lasting lubricating film. A combination of penetrating solvents, special greases, and corrosion inhibitors. This product contains PTFE.

### FEATURES

- Multi-purpose lubricant
- Penetrates
- Cleans
- Inhibits corrosion
- Color coded
- High viscosity
- Other features
- Contains PTFE

### BENEFITS

- Use on sliding mechanisms, chains, gears, bearings, and on other surfaces where friction, binding and sticking are a problem.
- Sprays on as a thin penetrating liquid that rapidly soaks in between surfaces, then cures to a longlasting lubricating film.
- Special solvents dissolve old grease and remove dirt as the product is being sprayed on.
- Protects metal surfaces by sealing out moisture, air, and other corrosive elements.
- Red in color to show how much and where the lubricant has been applied.
- After proper curing, the lubricant will not run, drip, or sag. Clings to vertical and overhead surfaces.
- Safe on all metals; effective at temperatures as high as 400°F (204°C)
- PTFE enhances lubrication performance and reduces friction.

### APPLICATIONS

Use to lubricate a variety of surfaces including chains, drive mechanisms, cables and wire ropes, tracks, conveyors, rollers, hinges, and similar moving surfaces.

### COMPANION PRODUCTS

Zep Aid NC, Zeplon, Zeprestore, Zep Big Orange, Zep Battery Coat, Zep Battery Care, Zep Hi-Lo Temperature Grease, Zep Viton Gloves, Zep Spectra Clear Glasses

### SPECIFICATIONS

Net Contents	1 lb. 2 oz. (511 g)	Non-volatile Materials	15% (by volume)
Flammability	Flammable - CSMA Flame Extension Method	Shelf Life	1 year minimum
Color	Red	D.O.T. Shipping Label	None
Flash Point	158° F (TOC)	Storage Temperature	15° - 130° F

### PACKAGING

20 fl. oz. Aerosol Can