

PRODUCT SPECIFICATION REPORT

High-Performance Lithium Grease is a multi-service fully synthetic oil-based grease. This grease provides the extended long service at continuously high operating temperatures and extreme pressure operations. This lithium complex soap and poly alpha olefin (POA) base oil combination provides extended life in sub-zero temperatures.

HIGH-PERFORMANCE LITHIUM GREASE

PROD. #3106



FEATURES/BENEFITS:

Synthetic PAO Base Oil	Suitable for high speed bearings running under different operating conditions
Superior Oxidation Resistance and Rust Protection	Extends equipment life in corrosive environments. The specialized additives present protect equipment from chemical oxidation rust and corrosion
Synthetic Oil Formulation	Allows for low temperature applications
Outstanding Extreme Pressure Protection	Provides effective wear protection for ball joints, drive shafts and other parts subjected to high pressure and shock loads
Excellent Water Resistance	Works effectively for extended periods of time under water ingress and in dusty/harsh environments

APPLICATIONS:

Recommended for high speed bearings at normal temperatures and medium speed bearings in colder climates. Effective in applications such as kiln car, wheel bearings, roller bearings, oven door hinges, pellet mill beatings, slag bed shaker bearings, oil and natural gas drilling, various manufacturing applications, and other industrial processes.

COMPANION PRODUCTS:

All-Purpose Lithium Grease, Pipe Dope/Anti-Seize, Morado Super Cleaner, Enviro 2000, Brake Wash, Brake Flush, Cherry Bomb, Reach

	NLGI Grade (ASTM D-217)	2
	Worked Penetration (ASTM D-217)	285
	Thickener Type	Lithium complex
	Color	Blue
_	Texture	Smooth, buttery, tacky (peanut butter
	Base Oil	Poly Alpha Olefin (PAO)

SPECIFICATIONS:

	2	
Worked Penetration (ASTM D-217)	285	
Thickener Type	Lithium complex	
Color	Blue	
Texture	Smooth, buttery, tacky (peanut butter texture)	
Base Oil	Poly Alpha Olefin (PAO)	
Temperature Range	-40° to 350°	
Rust Prevention D-1743 Rating	PASS	
Dropping Point (ASTM D-2265)	500°F	
4-Ball Weld Load (ASTM D-2596)	315 Kgf	
Timken OK Load (ASTM D-2509)	40 lbs	

Zep Sales & Service www.zep.com 1-877 I BUY ZEP

PACKAGING:

10 x 14 oz Cartridges–310604 40 x 14 oz Cartidges-310601 15 lb Pail-310615 40 lb Pail-310634 120 lb Keg-310642