




ZEP CLEANING SYSTEMS MINIMIZE WASTE, LOWER COSTS AND CLEAN CONSISTENTLY

HOW CAN A CLEANING SYSTEM MINIMIZE WASTE?

If your business cleans greasy metal parts, the generation and disposal of liquid waste is a responsibility you take seriously. Used, dirty solvents and detergents – some of which get classified as hazardous materials – create issues of liability and costly disposal that have a big impact on your bottom line.

Zep Manufacturing Company is a leader in developing parts cleaning systems that offer the latest technology and unique filtration systems to minimize the generation of liquid waste. High-performance parts washer and spray cabinet systems include specially-formulated, virgin-quality solvents and biodegradable detergents to help minimize impact on the environment.

Zep Parts Washers use a multi-stage filtering system that



reduces large quantities of liquid waste to a small amount of solid waste – solids which are easier to handle, transport and dispose of. The filtration process allows solvent to be used for a longer period of time, providing cost savings and consistent cleaning.

For larger cleaning applications, Zep Spray Cabinets utilize technology that keeps used hot water and detergents from going down the drain. The cabinets also have many safety features to save time and increase productivity.

Zep's knowledgeable sales representatives and technical experts are available to assist in verifying your generator status, increasing your cost savings, advising on filter disposal options and providing on-site training to implement a parts cleaning system that fits your business.

YOU'RE IN CONTROL, SO YOUR COSTS ARE LOWER

ELIMINATE MONTHLY RENTAL COSTS

Monthly parts washer rentals can result in high costs and uncertainty about your liability as a waste generator. Zep parts washers eliminate costly monthly fees because you own the unit. Solvent is used over an extended period of time and since you control the frequency of filter changes, costs are reduced. In addition, control is in your hands. You know the quality of the solvent used in your system and the status of the waste you generate.


Let Zep compare the cost between parts washer rental and ownership and help you pick the right combination of cleaning systems that will make your business more efficient.

ZEP LEASE-FINANCING PROGRAM


MAKES CLEANING SYSTEMS AFFORDABLE


Zep's affordable lease-financing program gives you the opportunity to buy the equipment you need today with monthly payments that are easy on your budget. At the end of the lease period, you own the equipment.

You can qualify for Zep's lease-financing program with low up-front costs, so you can hold on to valuable savings. It's the easy way to get all the equipment today that will keep you in business tomorrow.



HOW TO SELECT THE RIGHT PARTS WASHING SYSTEM





Dyna-Clean Parts Washer

#915201 Dyna-Clean Basin and Drum

#915301 Dyna-Clean Basin only

FEATURES

- All-steel construction
- Powder coat paint finish
- Tool-less assembly
- Spring-loaded lid for easy opening and closing
- 168 gph UL/CSA approved submersible electric pump which operates on 115 volt, 1 amp
- Model 5100 filtration system with 50-micron poly-propylene particulate filter with visible filter bowl
- Filter change indicator signals when the 5100 filter needs to be changed
- 165°F UL approved fire link. In the unlikely event of a fire, the link separates, permitting the lid to close — containing the fire
- Directional spout with on-off control
- Convenient tool rack

SPECIFICATIONS

Tank Size:	32" x 22" x 10"
Tank Capacity:	30 gallons
Overall Size:	32" x 22" x 40"
Weight:	122 lbs. with drum

SAFETY EQUIPMENT

892101	Nitrile Elbow Length Gloves, Size 9
892201	Nitrile Elbow Length Gloves, Size 10
770201	Spectra-Clear Safety Gloves
925501	Wilson Sport Safety Glasses
942301	Safety Faceshield
942601	Safety Polyethylene Cap

PRODUCTS TO USE

0366	Zep Dyna 143°
0179	Zep Dyna 170°
0369	Dyna Blue
F015	Dyna 680T2



The Zep Dyna-Clean is the standard by which most solvent-based parts washers are measured. Designed for fast, efficient and economical cleaning of dirty or greasy parts.

Zep's exclusive filtration system extends solvent life and helps protect the environment. Instead of large volumes of potentially-hazardous fluid hauled off from the work-site, only the filter elements are disposed of. The Zep Model 5100 filter can remove particles down to 10 microns (with optional element). The Dyna-Trap filter bag removes oils and greases — extending solvent life. Convenient Filter Change Indicator lets you know when it's time for a new filter.

FEATURES

STANDARD



SPRING-LOADED, FIRE-PROTECTIVE SAFETY LID utilizes a fusible link that melts at 160° to close the lid automatically in the event of a fire.



FLEXIBLE 24" PLASTIC SPOUT delivers solvent into the wash tank. The spout bends easily to allow access to hard-to-reach spots on parts.



REMOVABLE PLASTIC SINK STRAINER provides drainage and prevents large particles from falling into the solvent drum. When soaking parts use the **MAGNETIC DRAIN STOPPER** to maintain solvent level in the tank.



SUBMERSIBLE, CENTRIFUGAL PUMP is a rugged UL approved pump. Fittings and hoses are designed for years of trouble-free service.



Remove stubborn debris from parts with the **PARTS WASHING BRUSH**. When not in use, the brush can be stored on the lid.



DYNA TRAP FILTER SPOUT provides a convenient hook-up for operation of the Dyna Trap Filter Bag.




CONTROLS are conveniently located on the unit for easy access. Toggle switches operate the solvent pump. All wiring is 115 volt, corrosion resistant and three-wire safety grounded.



MODEL 5100 FILTER SYSTEM is mounted below the tank to allow easy access when the filter has to be replaced. The translucent styrene canister has an aluminum head.

FILTERS

- 904902** Replacement 5110 (10 micron) particulate filter element (box of two)
- 905502** Replacement 5150 (50 micron) particulate filter element (box of two)
- 900402** Replacement 5199 (100 micron) particulate filter element (box of two)
- 903402** Dyna-Trap filter bag (box of two)
- 916401** Dyna-Trap cover
- 916501** Dyna-Clean new work platform
- 907101** Dyna-Clean filter pad-new
- F77201** Dyna Blue Bowl



WORK PLATFORM



DYNA TRAP FILTER

ACCESSORIES

- 903501** Oriflo "Flow-Thru" Cleaning Brush
- 903001** 30 gallon Open Head Steel Drum
- 903701** Foot pedal switch
- 903901** Parts basket- 21.5" x 10.5" x 7.75"
- 906301** Work light

Centrifugal Filtration System for the Dyna-Clean Parts Washer

#F48501

FEATURES

- All metal construction.
- Baked-on enamel paint finish.
- High Volume 670 gph UL/CSA approved submersible electric pump.
- Pump operates on 115 volt, 3.2 amp.
- 90 micron cotton particulate filter with "through-the-drain" quick-change capability.

SPECIFICATIONS

Overall Size: Overall Size: 19" x 19" x 27".
Weight: 20 lbs.

SAFETY EQUIPMENT

892101 Nitrile Elbow Length Gloves, Size 9
892201 Nitrile Elbow Length Gloves, Size 10
770201 Spectra-Clear Safety Gloves
925501 Economy Safety Goggles
942301 Safety Faceshield
942601 Safety Polyethylene Cap


PRODUCTS TO USE

F48601 Replacement particulate filter element (box of five).



The Centrifugal Filtration System is designed to capture grease, soil, metal filings and other particulates before it reaches the solvent reservoir. This reduces the build up of sediment in the reservoir and the time consuming job of removal. The unique, pump-driven spinning action distributes the soil load evenly, increasing element life. The "through-the-drain" quick-change element makes routine maintenance simple and easy.

The Centrifugal Filtration System is the ideal selection for areas with high soil loads and works with the Zep Exclusive Dyna-Filtration System to extend solvent life and help protect the environment. Instead of large volumes of potentially hazardous fluid hauled off only the filter elements are disposed of. The Centrifugal Filtration System filter element can remove particles down to 90 micron. The 5100 filter can remove particles down to 10 micron (with optional element). The unique Dyna-Trap filter bag removes oils and greases- extending solvent life.



Dyna-Mate II Parts Washer

#F47201 electric pump
#F47601 air pump

FEATURES

- All steel construction.
- Baked-on enamel paint finish.
- Tool-less assembly.
- Spring loaded lid for easy opening and closing.
- Latched and sealed lid for solvent containment during transportation.
- Up to 168 gph UL/CSA approved electric pump operates on 115 volts.
- Up to 115 gph double-diaphragm air pump operates on 20 to 60 psi.
- 50 micron polypropylene particulate filter with visible filter bowl and filter condition indicator.
- 165° F UL approved fire link. In the unlikely event of a fire, the link separates, permitting the lid to close- containing the fire.
- Flow-through parts cleaning brush.
- Optional adjustable height rolling cart available for portability.

SPECIFICATIONS

Tank Size: 25" x 13-1/2" x 5"
Tank Capacity: 7 gallons
Overall Size: 31" x 15" x 14"
Weight: 39-1/2 lbs

ACCESSORIES

F47701 Adjustable height rolling cart
904902 Replacement 5110 (10 micron) particulate filter element(box of two)
905502 Replacement 5150 (50 micron) particulate filter element (box of two).
900402 Replacement 5199 (100 micron) particulate filter element (box of two)
903402 Dyna-Trap filter bag (box of two)
903501 Oriflo "Flow-Thru" Cleaning Brush
903701 Electric foot pedal switch
903901 Parts Basket- 21.5" x 10.5" x 7.75"

SAFETY EQUIPMENT

892101 Nitrile Elbow Length Gloves, Size 9
892201 Nitrile Elbow Length Gloves, Size 10
770201 Spectra-Clea Safety Gloves
925501 Wilson Sport Safety Glasses
942301 Safety Faceshield
942601 Safety Polyethylene Cap

PRODUCTS TO USE

0366 Zep Dyna 143°
0179 Zep Dyna 170°
0369 Dyna Blue
F015 Dyna 680 T2
1301 C-Solv



The Zep Dyna-Mate II is designed for areas where portability is a priority. Latchable, sealed lid makes it ideal for motorcycle shops and service trucks. An ideal selection for fast, efficient cleaning of small, dirty or greasy parts.

The Zep Exclusive Dyna-Filtration System extends solvent life and helps protect the environment. Instead of generating large volumes of liquid waste, only the filter elements are disposed of. The 5100 filter can remove particles down to 10 micron (with optional element). The unique Dyna-Trap filter bag removes oils and greases- extending solvent life.

Dyna-Brute FB Parts Washers

FEATURES

- All-steel construction
- Baked-on enamel paint finish
- Shelf removes for access to soaking area
- Spring-loaded lid for easy opening and closing
- 168 gph UL/CSA approved submersible electric pump which operates on 115 volt, 1 amp
- Model 5100 filtration system with 50-micron polypropylene particulate filter with visible filter bowl
- Filter change indicator signals when the 5100 filter needs to be changed
- 165°F UL approved fire link. In the unlikely event of a fire, the link separates, permitting the lid to close — containing the fire
- Directional spout with on-off control

SPECIFICATIONS

Tank Size:	36" x 24" x 28"
Tank Capacity:	35 gallons
Overall Size:	43" x 24" x 35.5"
Weight:	96 lbs.

SAFETY EQUIPMENT

892101	Nitrile Elbow Length Gloves, Size 9
892201	Nitrile Elbow Length Gloves, Size 10
770201	Spectra-Clear Safety Gloves
925501	Wilson Sport Safety Glasses
942301	Safety Faceshield
942601	Safety Polyethylene Cap

PRODUCTS TO USE


0366	Zep Dyna 143°
0179	Zep Dyna 170°

FILTERS

904902	Replacement Model 5110 (10 micron) particulate filter element (box of two)
905502	Replacement Model 5150 (50 micron) particulate filter element (box of two)
900402	Replacement Model 5199 (100 micron) particulate filter element (box of two)
906402	Replacement Model 51HH hog's hair filter element (box of two)
903402	Dyna-Trap filter bag (box of two)
907401	Dyna-Brute hogs hair filter pad

PRODUCTS TO USE


903501	Oriflo "Flow-Thru" Cleaning Brush
903701	Foot pedal switch
903901	Parts Basket- 21.5" x 10.5" x 7.75"
906301	Work Light



The Zep Dyna-Brute FB meets or exceeds the OTC Freeboard Specifications.

The New Zep Dyna-Brute is a tough, stable, parts washer for cleaning or soaking with solvent-based cleaners. An ideal choice for fast, efficient and economical cleaning of dirty or greasy parts. The Zep Dyna-Brute FB meets or exceeds the OTC Freeboard Specifications.

Zep's exclusive filtration system extends solvent life and helps protect the environment. Instead of having large volumes of potentially-hazardous fluid hauled off from the work-site, only the filter elements are disposed of. The Zep Model 5100 filter can remove particles down to 10 microns (with optional element). The Dyna-Trap filter bag removes oils and greases — extending solvent life. Convenient Filter Change Indicator lets you know when it's time for a new filter.



Zep PrestoKleen #907501

FEATURES

- All-steel construction
- Baked-on enamel paint finish
- Agitation operates using up to 3cfm of 20-100 psi compressed air.
- Positive sealing lid attaches to 7 gallon open head pail. Pail not included.

SPECIFICATIONS

Tank Capacity:	7 gallons
Overall Size:	13" diameter x 25"
Weight:	20 lbs.

ACCESSORIES

907801	7 gallon pail
908201	Replacement parts basket

SAFETY EQUIPMENT


892101	Nitrile Elbow Length Gloves, Size 9
892201	Nitrile Elbow Length Gloves, Size 10
770201	Spectre-Clear Safety Gloves
925501	Wilson Sport Safety Glasses
942501	Anti-Fog Safety Goggles
942301	Safety Faceshield
942601	Safety Polyethylene Cap

PRODUCTS TO USE

0362	Zepresto
5310	Zep XT-4990
0384	Carb-X



The Zep PrestoKleen is one of the most versatile agitating parts washers available. Capable of using standard or aggressive solvents, it is the ideal selection for fast, efficient cleaning of small dirty or greasy parts. Air driven agitating action permits operator to do other things, increasing productivity.



Zep Adjustable Brake Buggy

#930001

#955301 with filter kit

FEATURES

- All-steel construction
- Baked-on enamel paint finish
- Tool-less assembly
- Spring loaded lid
- Adjustable height from 13" to 50"
- Up to 115 gph double-diaphragm air pump operates on 20 to 60 psi
- Optional 50 micron polypropylene particulate filter with visible filter bowl and filter condition indicator
- 165° F UL approved fire link. In the unlikely event of a fire, the link separates, permitting the lid to close-containing the fire
- Flow-through parts cleaning brush with trigger control
- Low stable reservoir with large fill opening

SPECIFICATIONS

Tank Size: 24" x 26 - 1/2" x 5"
Tank Capacity: 5 gallons
Overall Size: 29" x 29" x 13"- 50"
Weight: 39-1/2 lbs.

ACCESSORIES

- 942101** Filter kit to add a 5100 filter system to an existing machine
- 904902** Replacement 5110 (10 micron) particulate filter element (box of two).
- 905502** Replacement 5150 (5 micron) particulate filter element. (box of two)
- 900402** Replacement 5199 (100 micron) particulate filter element. (box of two)

SAFETY EQUIPMENT

- 892101** Nitrile Elbow Length Gloves, Size 9
- 892201** Nitrile Elbow Length Gloves, Size 10
- 770201** Spectre-Clear Safety Gloves
- 925501** Wilson Sport Safety Glasses
- 942301** Safety Faceshield
- 942601** Safety Polyethylene Cap

PRODUCTS TO USE

- | | |
|----------------------------|---------------------------|
| 0505 Zep Brake Wash | 0366 Zep Dyna143° |
| 0570 Zep ID Red | 0179 Zep Dyna 170° |
| 0369 Dyna Blue | F015 Dyna 680 T2 |



The Zep Adjustable brake Buggy II is designed for areas where portability is a priority. An ideal selection for fast, efficient cleaning of brakes and small dirty or greasy parts. The optional Zep 5100 Filtration System extends solvent life by removing contaminants down to 10 micron (with optional element).

Super-Brute FB Parts Washer

FEATURES

- All-steel construction
- Baked-on enamel paint finish
- Stable X-leg design
- Shelf removes for access to soaking area
- Removable parts basket
- Spring-loaded lid for easy opening and closing
- 168 gph UL/CSA approved submersible electric pump operates on 115 volt, 1 amp
- Filter change indicator signals when the 5100 filter needs to be changed
- Model 5100 filtration system with 50-micron polypropylene particulate filter with visible filter bowl
- 165° F UL approved fire link. In the unlikely event of a fire, the link separates, permitting the lid to close — containing the fire
- Hog's hair filter pad in base of reservoir

SPECIFICATIONS

Tank Size:	43" x 24" x 28"
Tank Capacity:	45 gallons
Overall Size:	47.25" x 24.125" x 35.5"
Weight:	176 lbs

SAFETY EQUIPMENT

892101	Nitrile Elbow Length Gloves, Size 9
892201	Nitrile Elbow Length Gloves, Size 10
770201	Spectra-Clear Safety Glasses
925501	Wilson Sport Safety Glasses
942301	Safety Faceshield
942601	Safety Polyethylene Cap

PRODUCTS TO USE

0366	Zep Dyna 143°
0179	Zep Dyna 170°

FILTERS

904902	Replacement Model 5110 (10 micron) particulate filter element (box of two)
905502	Replacement Model 5150 (50 micron) particulate filter element (box of two)
900402	Replacement Model 5199 (100 micron) particulate filter element (box of two)
906402	Replacement Model 51HH hog's hair filter element (box of two)
903402	Dyna-Trap filter bag (box of two)
908601	Super-Brute hog's hair filter pad

ACCESSORIES

903501	Oriflo "Flow-Thru" Cleaning Brush
903901	Parts Basket- 21.5" x 10.5" x 7.75"
903701	Foot pedal switch
906301	Work Light



The New Zep Super-Brute FB is a tough, high-capacity, parts washer for cleaning or soaking with solvent-based cleaners. An ideal choice for fast, efficient and economical cleaning of large dirty or greasy parts. The Zep Super-Brute FB meets or exceeds the OTC Freeboard Specifications.

Zep's exclusive filtration system extends solvent life and helps protect the environment. Instead of having large volumes of potentially-hazardous fluid hauled off from the work-site, only the filter elements are disposed of. The Zep Model 5100 filter can remove particles down to 10 microns (with optional element). The Dyna-Trap filter bag removes oils and greases — extending solvent life. Convenient Filter Change Indicator lets you know when it's time for a new filter.

Dyna-100FB Agitating-Lift Parts Washer

FEATURES

SPECIFICATIONS

SAFETY EQUIPMENT

PRODUCTS TO USE

FILTERS

ACCESSORIES

Delivering Pure Solvent "On Demand" Every Day
GUARANTEED!



The Industry's Most Powerful Parts Cleaning Technology



MODEL 501



MODEL 571

The Power of Pure Solvent "On Demand" 4x Daily

SERIES 500 UNIQUE ADVANTAGES

- Recovers 100% of cleaning solvents
- Eliminates 100% of hazardous solvent waste
- Potentially reduces generator status
- No parts washer or recovery services required


WHY OPERATORS PREFER CLEAN SOLVENT

- Clean solvent cleans better
- Clean solvent cleans faster
- Clean solvent leaves less oily residue
- Clean solvent saves time and money





The Industry's Most Powerful Parts Cleaning Technology

	MODEL 501	MODEL 571	MODEL 110
General Description	On-site Recycling Parts Washer Standard Sink	On-site Recycling Parts Washer Large Sink	Portable Non-Recycling Parts Washer with Adjustable Height
60/30 RENTAL PROGRAM			
Initial 60 Mo. Rental Term	\$99.00	\$109.00	\$29.00
Optional 30 Mo. Renewal Term	\$49.50	\$54.50	\$14.50
Purchase Option	Prepayment of the Initial Term		
Warranty	5 Year Comprehensive Parts and Labor		
Specifications			
Overall Dimensions	68" h x 32" w x 27" d	70" h x 39" w x 29" d	58"-72" h x 33" w x 21" d
Working Area (w x d)	32" x 27"	39" x 29"	26.5" x 17"
Working Height	34"	34"	33"-47" Adjustable
Operation	Push Buttons: On/Off, Recycle	Push Buttons: On/Off, Recycle	Push Buttons: On/Off
Solvent Capacity	20 Gallons	20 Gallons	1 Gallon
Typical Recycle Time	4 Hours	4 Hours	N/A
Power Requirements	115 VAC, 11.9 Amps, 60 Hz	115 VAC, 11.9 Amps, 60 Hz	115 VAC, 1 Amp, 60 Hz
Weight	326 lbs	342 lbs	142 lbs
Construction	Heavy gauge steel throughout	Heavy gauge steel throughout	 <p>MODEL 110 Telescoping mobile washer</p>
Safety Features	Fuse protection Dual temperature sensor Fusible link Temperature sensitive decal	Fuse protection Dual temperature sensor Fusible link Temperature sensitive decal	


HOW THE INTEGRATED MICRO-REFINERY WORKS

TRANSFER PROCESS (4 minutes)

1. DIRTY SOLVENT FLUSHED INTO THE DISTILLATION CHAMBER.
2. CLEAN SOLVENT TRANSFERRED INTO WASH BASIN AND AVAILABLE FOR IMMEDIATE USE.

RECYCLE PROCESS (4 hours)

3. DIRTY SOLVENT HEATED UNDER VACUUM TO VAPOR POINT.
4. SOLVENT VAPORIZED.
5. OILY RESIDUE SEPARATED FROM VAPORIZED SOLVENT FOR PERIODIC REMOVAL.
6. SOLVENT VAPORS COOLED BACK TO LIQUID STATE IN CONDENSER.
7. 100% PURE SOLVENT RETURNED TO RESERVOIR AND AVAILABLE FOR CONTINUED USE.



Dyna Green 35 Heavy Duty Aqueous Parts Washer #F03701

FEATURES

SPECIFICATIONS

SAFETY EQUIPMENT

PRODUCTS TO USE

FILTERS

ACCESSORIES



Zep Spray Cabinets

FEATURES

- Dry-floor evaporation system for waste minimization on all "E" models
- Certified to UL and CSA standards
- Fixed jets and spray bar use all the impact force for cleaning, not driving the spray bar
- Upright configuration takes up less space and is easier to load
- Heavy 10- or 12-gauge steel construction for durability
- High load weight capacity for more parts per cleaning cycle
- Up to 50% of load capacity can be suspended from top frame. This means tall, heavy items like machine parts and cylinder heads can be secured upright for cleaning
- Main turntable support bearing is outside the cabinet for protection from the cleaning action
- Stainless steel "air shield" door cover for operator protection
- Seal-less, octagonal "EZ Load" door with heavy-duty hinge pins for easy loading
- V-belt driven turntable for overload protection. Prevents motor damage in case of a jam
- Flush seal or seal-less pump for durability



Zep Spray Cabinets are durable, high-performance machines built for the professional. All spray cabinets are special order.

SPECIFICATIONS

Model	2040E	2055E	2085E	2085TE	2175E	2260E	2260TE
Zep Product Number	F22301	F22801	F22201	F22101	F22001	F22601	F22401
Evaporation System	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Water capacity	40 gal	55 gal	85 gal	85 gal	175 ga	260 gal	260 gal
Motor	2 hp	3 hp	3 hp	5 hp	7.5 hp	15 hp	20 hp
Voltage	230v	230v	230v	230v	230v	230v	220v
Phase	1 ph	1 ph	1 ph	1 ph	3 ph	3 ph	3ph
Amps Required	30 amps	60 amps	60 amps	60 amps	80 amps	80 amps	100 amps

Pump	Flush Seal Pump		Seal-less Pump				
Load capacity	1,000 lbs.	1,000 lbs.	1,500 lbs.	1,500 lbs.	2,000 lbs.	3,500 lbs.	3,500 lbs.
Load height	31"	31"	41"	51"	54"	72"	102"
Turntable Dia.	24"	24"	28"	28"	40"	52"	52"
Basket	STD	STD	STD	STD	STD	STD	STD
Door cover	S.S.	S.S.	S.S.	S.S.	S.S.	S.S.	S.S.
Seal-less door	STD	STD	STD	STD	STD	STD	STD
Heaters	7 kw	7 kw	10 kw	12 kw	24 kw	30 kw	30 kw
Oil skimmer	STD	STD	STD	STD	STD	STD	STD
Gauge steel	12 ga	10 ga	10 ga	10 ga	10 ga	10 ga	10 ga
Dimensions							
Length	40"	40"	42"	42"	53"	87"	87"
Width	44"	44"	61"	61"	78"	91"	91"
Height	75"	75"	89"	97"	96"	126"	156"
Shipping weight	665 lbs.	945 lbs.	1,080 lbs.	1,250 lbs.	1,820 lbs.	3,070 lbs.	3,400 lbs.
Number of 0" Spray Jets	56	56	72	85	124	168	208

S.S. - Stainless Steel STD - Standard OPT - Optional • 2055E and larger units need to be direct wired. 2020,2020E and 2040E have plugs

SAFETY EQUIPMENT

- 892101** Nitrile Elbow Length Gloves, Size 9
- 892201** Nitrile Elbow Length Gloves, Size 10
- 942401** Spectra-Clear Safety Glasses

- 925501** Economy Safety Goggles
- 942301** Safety Faceshield
- 942601** Safety Polyethylene Cap

FACTORY INSTALLED

Factory Installed Options:

- Natural Gas Heating System (2085E, 2085TE, 2175E, 2260E, 2260TE)
- Propane Gas Heating System (2085E, 2085TE, 2175E, 2260E, 2260TE)
- Hourmeter Kit
- 230 Volt, 3 Phase Operation
- 460 Volt, 3 Phase Operation
- Small Internal Spray Bar kit (2040E, 2050E, 2085E, 2085TE): adds another spray bar and two tier baskets.
- Large internal Spray Bar Kit (2175E, 2260E, 2260TE): adds another spray bar and two tier baskets.
- Stainless Steel automatic water level tank with low water shut off kit: maintains correct water level in cabinet
- Automatic Oil Skimmer Kit: includes electric solenoid and 7 day, 1 channel timer
- 7-day Timer
- "Why Worry About It" Kit (All 'E' Models): includes Stainless Steel Standard automatic oil skimmer with electric solenoid and a 7-day, 2 channel, digital timer
- Parts Basket - 10 1/4" dia 12" tall
- Parts Basket with lid - 10 1/4" dia 12" tall
- Small Transmission Parts Tree (All Models)
- Large Transmission Parts Tree (2085TE, 2175E, 2260E, 2260TE)
- Heavy-Duty Wheel Kit (2020, 2020E, 2040E)

ZEP SPRAY CABINETS: MODELS & CLEANERS

ZEP SPRAY CABINET DETERGENTS

PRODUCT	TYPE	PERFORMANCE	FORM	FOAM LEVEL	CONCENTRATION	TEMP.
Recirculating Detergent - #0363	Aluminum	Light to medium	Powder	Low (>140°F)	1/16 - 1/8 lb./gal	160°F
Split Recirculating Detergent - #0658	Aluminum	Light to medium	Powder	Low	1/8 - 1/2 lb./gal	160°F
Round Robin - #7908	Aluminum	Light to medium	Liquid	Low	2% - 10% by volume Aluminum 2%-6% 140 - 170 Ferrous 2%-10% 140 - 200	160°-200°F
Formula 15282 - #5348	Aluminum	Medium	Powder	Low	1/8 lb./gal	160°F
R-15681 - #5359	Aluminum	Light to medium	Liquid	Low	2 qt./gal	160°
Formula 11263 - #0615	Ferrous	Heavy duty	Powder	Low	0 lb./gal	160°-200°F
Formula 12475 - #0614	Ferrous	Heavy duty	Powder	Low	1/8 to 1lb./gal	180°-200°F
Zep LSW - #7914	Ferrous	Heavy duty	Liquid	Low	1/8 to 1lb./gal	160°-200°F