



Superior Solutions

PROD. #K613  
808

## PRODUCT SPECIFICATION REPORT

### SELIG

# RED-E-LUBE

## All Purpose Grease

#### DESCRIPTION

Red-E-Lube is an all purpose, non-melt bentonite grease formulated with extreme pressure and anti-wear additives to provide heavy duty service.

#### FEATURES

- Extreme tackiness
- Temperature stable
- Extreme pressure additive
- Superior protection
- Special rust and corrosion inhibitors
- Outstanding resistance

#### BENEFITS

- Will not sling off, which can cause loss of product and effectiveness
- Performs in temperatures from -10°F and up to 550°F
- Excellent load carrying capability, 65lb. Timken Load
- Red-E-Lube protects equipment both indoors and outdoors under high temperature and high pressure
- Prevents rust and corrosion and the resulting seizing of fittings
- Resistant to water, acids, salt-spray, weather, dust, dirt and oxidation

#### APPLICATIONS

Recommended for:

Automotive Repair Shops  
Construction Companies  
Electrical Contractors

Fabricated Metal Shops  
Industrial Machinery Manufacturers  
Marine Products

Motorcycle Dealers  
New & Used Car Dealers  
Service Stations

#### COMPANION PRODUCTS

Zep Big Orange, Zep Tuff Green, Zep Preserve, Zep Solv, Zep Top Solv, Zep 45, Zep Soy Response, Zep Orange Gel Degreaser, Zep Soy Cling

#### SPECIFICATIONS

Physical form	Solid (gel)	Flash point (open cup)	400°F
Odor	Petroleum-like	pH	N/A
Color	Red	Shelf life	1 Year Minimum
Specific Gravity	0.8	DOT Shipping label	None
NLGI Grade	2	Dropping Point (ATSM D-556)	550°F (non-melt)
Water Resistance	Excellent	Penetration (ASTM D-217)	260-295
Rust Resistance	Excellent	Timken OK Load (ASTM D-2509)	65 Lb.
Acid Resistance	Excellent		

#### PACKAGING

14 oz. tube/case of 12  
120 lb. drum  
420 lb. drum

Zep Sales & Service, a unit of Zep Inc.

1-877-I BUY ZEP  
(1-877-428-9937)



Superior Solutions

## PRODUCT LABEL

PROD. #K613  
808

### SELIG

## RED-E-LUBE

### All Purpose Grease

# RED-E LUBE

RED-E LUBE is an all purpose non-melt grease especially formulated with extreme pressure and anti-wear additives to provide heavy duty service. It is one of very few greases able to withstand heavy shock load and impact pressures of 65 Timken load capabilities. This product has excellent adhesive and cohesive properties. It resists most acids, weather, dirt, salts spray, steam and oxidation. Our product protects equipment indoors or outdoors even under high temperatures and heavy loads.

#### USER BENEFITS

1. Exceptional resistance to acids, water, salt spray, weather, dirt, steam and oxidation.
2. Exceptional adhesive-cohesive and anti wear properties.
3. Gives Extra "cushioning" that reduces shock and noise.
4. Performs at a wide variety of temperatures up to 550°F.
5. Excellent outdoor resistance, extreme pressure and high heat resistance. Water resistant too.
6. High Shock and impact resistance. No pound out or thin out.
7. Seals out dust-dirt-contaminants, prolongs life of metal parts.
8. Contains special corrosion and rust inhibitors.
9. Excellent load carrying capacity - 65 timken load.

#### USES

Automotive  
Sugar Cane Mills  
Marine  
Elevators  
Aircraft  
Sewage Plants

Farms  
Dairies  
Oil Fields  
Textile Plants  
Lumber Mills

Bottling Plants  
Paper Mills  
Steel Mills  
Construction  
Cement Plants

Cotton Gins  
Industrial  
Air Conditioning  
Mining  
Food Plants

**PUMP IN RED-E LUBE UNTIL ALL OLD GREASE COMES OUT.**

**BOMBLEAR RED-E LUBE HASTA QUE TODA LA VIEJA GRASA SE DESPRENDA.**

### CAUTION:

KEEP OUT OF REACH OF CHILDREN. Do not take internally. Do not ingest. If this should occur, drink large volumes of water and seek medical attention. Avoid storage of product in freezing temperatures. Discard according to federal, state and local regulations. KEEP OUT OF REACH OF CHILDREN.

**CAS Numbers:** Petroleum Distillate 8002-05-9; Rheological Thickener 68953-58-2; N.J.# 800983-5015P.  
**HMIS RATING:** Health-1; Flammability-1; Reactivity- 0; Personal Protection-B.

Manufactured For:



Proudly American Made  
**SELIG INDUSTRIES**

A division of Acuity Specialty Products Group, Inc.  
**ATLANTA, GA 30336**

**AcuityBrands.**

To Reorder Call, 1-800-447-3544

\*2151

NET WT. 14 OZ.(397 grams)

Zep Sales & Service, a unit of Zep Inc.

1-877-I BUY ZEP  
(1-877-428-9937)