

Version 1.5

Revision Date 03/20/2017

Print Date 11/28/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	ZEP 45 DUAL FORCE AERO DZ
Material number	:	0000000000374301
Manufacturer or supplier's d	eta	ils
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	amber
Odour	characteristic

GHS Classification

Flammable aerosols Gases under pressure	: Category 1 : Compressed gas
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated.
Precautionary statements	 Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. Storage:



	-	
Version 1.5	Revision Date 03/20/2017	Print Date 11/28/2017

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place. **Disposal:** Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration [%]
64742-47-8	>= 50 - < 70
64742-52-5	>= 10 - < 20
88917-22-0	>= 1 - < 5
124-38-9	>= 1 - < 5
	64742-47-8 64742-52-5 88917-22-0

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
lf inhaled	:	If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a physician or poison control center. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation.
Notes to physician	:	Treat symptomatically. Symptoms may be delayed.



Version 1.5

Revision Date 03/20/2017

Print Date 11/28/2017

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	 For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours or spray mist.
	Avoid exposure - obtain special instructions before use.
	Avoid contact with skin and eyes.
	For personal protection see section 8.



Version 1.5	Revision Date 03/20/2017	Print Date 11/28/2017
	Smoking, eating and drinking shou application area. Take precautionary measures aga Provide sufficient air exchange an Dispose of rinse water in accordar regulations. Always replace cap after use.	inst static discharges. d/or exhaust in work rooms.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. exposure and temperatures over & or throw into fire even after use. D red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventila Electrical installations / working m the technological safety standards 	50 °C. Do not open by force o not spray on flames or ated place. aterials must comply with
Materials to avoid	: Oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA PO
		STEL	30,000 ppm 54,000 mg/m3	OSHA PO
		PEL	5,000 ppm	CAL PEL

Components with workplace control parameters

SAFETY DATA SHEET



ZEP 45 DUAL FORCE AERO DZ

sion 1.5	Revision Dat	te 03/20/2017	Print Da	ate 11/28/201
	1		9,000 mg/m3	
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
Engineering measures	: effective vent	ilation in all pro	ocessing areas	
Personal protective equip	nent			
Respiratory protection	ventilation is	provided or ex	nless adequate local posure assessment c commended exposur	lemonstrates
Hand protection Material Remarks	•	y for a specific	workplace should be otective gloves.	discussed
Eye protection	: Safety glasse	es		
Skin and body protection		protection acc	cording to the amount	
Hygiene measures	When using o	do not eat or di do not smoke. before breaks	rink. and at the end of wor	·kday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a compressed gas
Colour	:	amber
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	Not applicable
Boiling point	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.8715 g/cm3
Solubility(ies)		

SAFETY DATA SHEET



ZEP 45 DUAL FORCE AERO DZ

Version 1.5	Revision Date 03/20/2017	Print Date 11/28/2017
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: >20 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects may be delayed, symptoms may include minor eye or skin irritation.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.



ersion 1.5	Revision Date 03/20/2017	Print Date 11/28/201
NTP	No component of this product present equal to 0.1% is identified as a known by NTP.	
ute toxicity		
Product:		
Acute dermal toxicity	: Acute toxicity estimate : 3,722 mg/ Method: Calculation method	kg
Components:		
Distillates (petroleum), hyd Acute oral toxicity	rotreated light: : LD50 Rat: > 5,000 mg/kg	
Acule oral loxicity	. LD50 Kat. > 5,000 mg/kg	
Acute inhalation toxicity		
	Exposure time: 6 h	
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
Distillates (petroleum), hyd	rotreated heavy naphthenic:	
Acute oral toxicity	: LD50 Rat: > 5,000 mg/kg	
Acute inhalation toxicity	: LC50 Rat: > 5 mg/l	
	Exposure time: 4 h	
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg	
in corrosion/irritation		
Product:		

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Distillates (petroleum), hydrotreated light: Distillates (petroleum), hydrotreated heavy naphthenic: Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate:



Version 1.5

Revision Date 03/20/2017

Print Date 11/28/2017

carbon dioxide:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light: Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water	: Remarks: No data available
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SAFETY DATA SHEET



ZEP 45 DUAL FORCE AERO DZ

Version 1.5

Revision Date 03/20/2017

<u>Components:</u> Distillates (petroleum), hydrotreated light :

Additional ecological : No data available information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.



Version 1.5

Revision Date 03/20/2017

Print Date 11/28/2017

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
pentyl acetate	628-63-7	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Sudden Release of Pressure Hazard Fire Hazard	
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65	WARNING! This product contains a chemical known to the State of California to cause cancer.	
naphthalene	91-20-3	
The components of this product are reported in the following inventories:		
	SCA Inventory of this product are on the Canadian DSL	
For information on the country notification status for other regions please contact the		

manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION




Version 1.5

Revision Date 03/20/2017

Print Date 11/28/2017





OSHA - GHS Label Information:

Hazard pictograms	
Signal w ord Hazard statements Precautionary statements	 Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not
	pierce or burn, even after use. Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a w ell-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.5
Revision Date:	03/20/2017
Print Date:	11/28/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.